

MF2400B Series

Microwave Frequency Counter

10 Hz to 20/27/40 GHz



The Most up to Date Comprehensive Frequency Measurement Available

Latest Burst Wave Measurement

The line up of MF2400B series is composed of three frequency counters: the MF2412B (20 GHz), the MF2413B (27 GHz), and the MF2414B (40 GHz).

They are ideal for evaluating mobile radio communications devices and circuits, and are also able to measure the carrier frequency and pulse width of burst signals.

In addition to displaying measurements results on a 12-digits LCD, the frequency values can be read using the analog display function, which can be used for monitoring

evaluation and especially for frequency adjustment, etc., of various types of oscillators.

Furthermore, the template function is useful for assessing whether or not the measurement results fall within the upper and lower frequency limit specifications; the evaluation result is output from the AUX connector on the rear panel as Go/No-go signal. An easy-to-use automatic measurement system can be configured using the GPIB function.







Wide Band Measurement

The line up of three counters upper frequency limits of 20, 27, and 40 GHz meet every type of usage requirement. In addition, a high-frequency fuse holder and fuse element protect the input circuit from excessively powerful signals, and a variety of adapters are available for coupling each connector.


High-Accuracy Burst Measurement

The carrier frequency, burst width and burst repetition rate of a 100 ns to 0.1 s burst signal input from INPUT 1 can be measured quickly at high accuracy.

Measurement	Positive selected	Negative selected
Burst width	 Measurement at Burst ON time	 Measurement at Burst OFF time
Burst repetition	 Measurement of On-On period	 Measurement of Off-Off period

Analog Display Function

Using this function, the entire LCD becomes an analog meter and the measured values are indicated by the position of the meter needle. In addition to grasping changes in the measured frequency, this permits faster frequency adjustment and Go/No-go judgement of oscillators which had to be read many digits of measured data before. This analog meter also solves problems of misreading of frequency value.



Moves left/right and indicates frequency value

Template Function


When the upper and lower frequency limits have been preset, if the measured frequency is within the preset range, Go is displayed; if it is out of range, No-go is displayed. In addition, the Go/No-go signal can be output from the AUX connector on the back panel as a TTL signal.

This is very useful for configuring an automatic device Pass/Fail evaluation system (using analog display).

High-Speed Transient Measurement

Frequency counters have an interval when measurement is not performed (sample rate), so that sudden frequency changes during this period can not be measured.


However, the MF2400B series overcomes this problem by capturing frequency changes at speeds of up to 10 μ s and saving a maximum of 2000 sampling points. When it is combined with a host computer, frequency changes can be displayed graphically. This is very effective for measuring VCO start-up characteristics and PLL lock times.



Gating Function


At burst signal measurement, the carrier frequency may be different at the start, middle, and end of the burst.


In the MF2400B series, the carrier signal frequency at any position of the signal (delay time from trigger signal leading edge) and at any specified time (gate time) can be measured using a combination of the gating and trigger delay functions.



Save and recall functions added

Up to maximum of 10 setups can be stored in the internal memory, and these can be freely recalled. Storing complex setups in advance, such as burst triggers and gate settings, makes it possible to recall them immediately when needed for measurement, which makes it possible to reduce the measurement setup time and to prevent malfunctions from setup mistakes.





① 248 x 60 dot LCD displaying measurement results and parameter settings.

② **Sample Rate**

Sets measurement off time

③ **Resolution**

At normal measurement, the ◀ and ▶ keys switch the frequency measurement resolution. However, when setting parameters, the ◀ and ▶ keys are used to select the setting item; the selected item is confirmed by pressing the Enter key.

④ **Menu**

This key sets measurement functions such as frequency, level and burst, etc. It automatically changes to the parameter setting condition, and changes numerics and units.

⑤ **Preset**

Pressing this key returns each parameter to the initial setting.

⑥ **Hold, Restart**

The Hold key is used to hold to measured valued. When Hold is ON, the key lamp is lit. The Restart key starts measurement over. When the Restart key is pressed when Hold is ON, the latest data is measured and hold.

⑦ **Frequency Acquisition**

This is used at frequency measurement of Input 1. At Auto, the full frequency band is swept and the frequency of signals exceeding the specified level is measured. At Manual, the preset frequency and the frequency in input allowable frequency range can be measured.

⑧ **Meas Mode**

At Burst, the burst signal width, period and carrier frequency can be measured (not related to Acquisition key setting, and change in to the manual measurement condition). Continuous wave measurement is performed at CW mode.

⑨ **Return to Meas**

Pressing this key after setting parameters, returning the counter to the normal measurement status.

⑩ **Ext Trig Input**

Measures frequency by using external timing signal

⑪ **AUX Output**

Outputs control signal of the measurement function and parameters which are set.



Specifications

MF2400B Series

Input	Frequency range	INPUT 1 MF2412B: 600 MHz to 20 GHz MF2413B: 600 MHz to 27 GHz MF2414B: 600 MHz to 40 GHz INPUT 2 10 MHz to 1 GHz (50 Ω), 10 Hz to 10 MHz (1 MΩ)																
	Input level range (sine wave input)	INPUT 1 -33 to +10 dBm (<12.4 GHz), -28 to +10 dBm (<20 GHz), -25 to +10 dBm (<27 GHz), [-44.6 + 0.741 x frequency (GHz)] to +10 dBm (≤40 GHz) INPUT 2 25 mVrms to 2 Vrms (50 Ω), 25 mVrms to 10 Vrms (1 MΩ)																
	Impedance, coupling	INPUT 1: 50 Ω, AC couple INPUT 2: 50 Ω or ≥1 MΩ (≤35 pF), AC couple																
	Connector	INPUT 1 MF2412B: N-type, MF2413B: SMA-type, MF2414B: K-type INPUT 2: BNC-type																
Gating function	Trigger mode	INT: Triggered by measurement signal EXT: Triggered by external signal *Trigger level: 1.5 V ± (2 to 10 Vp-p), Trigger pulse width: ≥1 μs, Impedance: ≥100 Ω, Coupling: DC LINE: Triggered by AC line signal																
	Trigger delay	20 ns to 0.1 s*1, off (≤320 ns in 20 ns steps, and <1 μs in 40 ns steps variable; ≥1 μs in continuously variable as effective two digits)																
	Gate width	100 ns to 0.1 s (<1 μs in 20 ns steps variable; ≥1 μs in continuously variable as effective two digits)																
Pulse modulation wave measurement	Frequency range	MF2412B: 600 MHz to 20 GHz MF2413B: 600 MHz to 27 GHz MF2414B: 600 MHz to 40 GHz																
	Pulse width	100 ns to 0.1 s (NARROW), 1 μs to 0.1 s (WIDE)																
	Pulse repetition frequency	10 Hz to 4 MHz (pulse off time: ≥240 ns)																
	Carrier frequency measurement*2	Max. resolution: 10 kHz (pulse width: 100 ns to 1 μs), 1 kHz (pulse width: 1 to 10 μs), 100 Hz (pulse width: 10 to 100 μs), 10 Hz (pulse width: 0.1 to 1 ms), 1 Hz (pulse width: 1 to 10 ms), 0.1 Hz (pulse width: 10 to 100 ms) Measurement time: $(T \text{ or } T_s \text{ whichever is greater}) \times \{1/(f_R \times TGW)\}^2$ *3 <table border="1"> <thead> <tr> <th>Resolution</th> <th>1 Hz</th> <th>10 Hz</th> <th>100 Hz</th> <th>1 kHz</th> <th>10 kHz</th> <th>100 kHz</th> <th>1 MHz</th> </tr> </thead> <tbody> <tr> <td>Measurement time</td> <td>200 s</td> <td>20 s</td> <td>2 s</td> <td>200 ms</td> <td>20 ms</td> <td>5 ms</td> <td>5 ms</td> </tr> </tbody> </table> *Measurement carrier frequency: 1 GHz (TGW*3 = 0.1/f _R) Accuracy: ±1 count ±time base accuracy x measurement frequency ±trigger accuracy ±residual error*5 ±1/TGW*3	Resolution	1 Hz	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	1 MHz	Measurement time	200 s	20 s	2 s	200 ms	20 ms	5 ms	5 ms
	Resolution	1 Hz	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	1 MHz										
Measurement time	200 s	20 s	2 s	200 ms	20 ms	5 ms	5 ms											
Pulse width measurement	Resolution: 1 ns Accuracy: ±20 ns ±time base accuracy x measurement pulse width ±trigger accuracy Unit indication: μs (fixed)																	
Pulse period measurement	Resolution: 1 ns Accuracy: ±20 ns ±time base accuracy x measurement period ±trigger accuracy Unit indication: μs (fixed)																	
Carrier wave frequency measurement	Resolution, gate time	INPUT 1 NORMAL: 1 MHz/1 μs to 0.1 Hz/10 s FAST: 1 MHz/0.18 μs to 0.1 Hz/1.8 s (typical) INPUT 2 10 MHz to 1 GHz (50 Ω): 1 MHz/1 μs to 0.1 Hz/10 s 10 Hz to 10 MHz (1 MΩ): Shown below 																
	Measurement accuracy	INPUT 1 NORMAL: ±1 count ±time base accuracy x measurement frequency ±residual error*4 FAST: ±1 count ±time base accuracy x measurement frequency ±trigger accuracy ±residual error*5 INPUT 2 10 MHz to 1 GHz: ±1 count ±time base accuracy x measurement frequency 10 Hz to 10 MHz: ±1 count ±time base accuracy x measurement frequency ±trigger accuracy																

Auto/manual measurement	Auto FM tolerance: 35 MHzp-p, Acquisition time: ≤50 ms Manual (CW measurement) Input allowable frequency range: ±30 MHz (600 MHz to 1 GHz), ±40 MHz (≥1 GHz) Acquisition time: ≤15 ms Manual (Burst measurement) Input allowable frequency range: ±30 MHz (600 MHz to 1 GHz, pulse width mode: WIDE) ±20 MHz (≥1 GHz, pulse width mode: NARROW) ±40 MHz (≥1 GHz, pulse width mode: WIDE) Acquisition time: ≤15 ms
Functions	Template: Inputs in upper/lower limit of frequency, judged on GO/NO-GO Frequency offset: +offset, -offset, ppm Statistical processing: mean, maximum, minimum, p-p Save/recall: 10 panel settings (max)
AUX output	Output for GO/NO-GO, count end, input level detection, internal gating, restart, and acquisition signal
Sample rate	1 ms to 10 s (1-2-5 steps), hold
High-speed sample period/frequency resolution	INPUT 1: 10 μs/10 kHz, 100 μs/1 kHz, 1 ms/100 Hz INPUT 2: 10 μs/100 kHz, 100 μs/10 kHz, 1 ms/1 kHz *Measurement frequency : 100 MHz
Memory back up	Store in non-volatile memory at instrument power-down
Display	Display digits: 12 digits and 1 digit (- mark) LCD: 248 x 60 dots (with back light)
Reference crystal oscillator	Frequency: 10 MHz Warm-up: ≤±5 x 10 ⁻⁹ /day (after 30 min. warm-up) Aging rate: ≤±2 x 10 ⁻⁸ /day (after 24 h warm-up) Temperature characteristics: ±5 x 10 ⁻⁸ (0° to 50 °C)
External reference input	1/2/5/10 MHz, Input voltage: 1 to 5 Vp-p (AC coupling), Input impedance: ≥1 kΩ
External reference output	1/2/5/10 MHz*6, Output voltage: ≥2 Vp-p (open end, AC coupling), Output impedance: ≤400 Ω
External control	GPIO (conforms to IEEE488.2 standards): SH1, AH1, T5, L4, SR1, RL1, PPO, DC1, DT1, C0, E2
Power	85 to 132/170 to 250 V (auto switch), 47.5 to 63 Hz, ≤80 VA
Operating temperature	0° to 50 °C
Dimensions and mass	213 (W) x 88 (H) x 350 (D) mm, ≤5 kg
EMC	EN55011: 1191, Group 1, Class A EN50082-1: 1992
Safety	EN61010-1: 1993 (Installation Category II, Pollution Degree II)

*1 Delay time until counter started by trigger detection

*2 MANUAL measurement mode

*3 f_r: frequency resolution, TGW: gate width, T_s: processing time (50 μs), T: period (2/f_r)

*4 Measurement frequency (GHz)/10 count (rms)

*5 Measurement frequency (GHz)/2 count (rms)

*6 10 MHz when using internal reference signal; outputs signal based on this signal (1/2/5/10 MHz) when using external reference signal

● Options 01/02/03: Crystal oscillator

Option number	01	02	03
Frequency	10 MHz		
Aging rate	5 x 10 ⁻⁹ /day, 5 x 10 ⁻⁹ /month, 7.5 x 10 ⁻⁸ /year *After power on, with reference to frequency after 24 h	2 x 10 ⁻⁹ /day, 3 x 10 ⁻⁹ /month, 4.5 x 10 ⁻⁸ /year *After power on, with reference to frequency after 24 h	5 x 10 ⁻¹⁰ /day, 1 x 10 ⁻⁹ /month, 1.5 x 10 ⁻⁸ /year *After power on, with reference to frequency after 48 h
Temperature characteristics	±5 x 10 ⁻⁸	±1.5 x 10 ⁻⁸	±5 x 10 ⁻⁹
	-10° to 60 °C (with reference to 25 °C)		

Ordering information

Please specify model/order number, name and quantity when ordering.

Model/order No.	Name	Remarks
MF2412B MF2413B MF2414B	<p>– Main frame –</p> Microwave Frequency Counter Microwave Frequency Counter Microwave Frequency Counter	10 Hz to 20 GHz, N-J connector 10 Hz to 27 GHz, SMA-J connector 10 Hz to 40 GHz, K-J connector
F0012 W1520AE	<p>– Standard accessories –</p> Power cord, 2.5 m: 1 pc Fuse, 3.15 A: 2 pcs MF2412B/2413B/2414B operation manual: 1 copy	
MF2412B-01 MF2413B-01 MF2414B-01 MF2412B-02 MF2413B-02 MF2414B-02 MF2412B-03 MF2413B-03 MF2414B-03	<p>– Options –</p> Crystal oscillator (5 x 10 ⁻⁹ /day) Crystal oscillator (5 x 10 ⁻⁹ /day) Crystal oscillator (5 x 10 ⁻⁹ /day) Crystal oscillator (2 x 10 ⁻⁹ /day) Crystal oscillator (2 x 10 ⁻⁹ /day) Crystal oscillator (2 x 10 ⁻⁹ /day) Crystal oscillator (5 x 10 ⁻¹⁰ /day) Crystal oscillator (5 x 10 ⁻¹⁰ /day) Crystal oscillator (5 x 10 ⁻¹⁰ /day)	
K224*1 34RKNF50 J0526 J0527 J0127A J0853 J0854 MP612A*2 MP613A*2 J0007 J0008 B0426A B0409 B0329L J0060 B0390G B0411A ERV713-H J0997	<p>– Optional accessories –</p> Coaxial adapter (K-P•K-J, SMA compatible) Coaxial adapter (ruggedized K-P•N-J) Coaxial adapter (N-J•SMA-J) Coaxial cord (K-P•K-P), 2 ft Coaxial cord (BNC-P•RG-58A/U•BNC-P), 1 m Coaxial cord (N-P•SF104P•N-P), 2 m Coaxial cord (APC3.5-P•SF104P•APC3.5-P), 2 m Fuse Holder (N-P•N-J) Fuse Element GPIB cable, 1 m GPIB cable, 2 m Carrying bag Carrying case Protection cover Coaxial adapter (N-J•SMA-P) Rack mount kit Rack mount kit Portable power supply Adapter	DC to 40 GHz, SWR: 1.2 DC to 20 GHz, SWR: 1.25 DC to 1 GHz DC to 1 GHz, Power rating: +17 dBm, Blow rating: ≥+35 dBm Soft type With B0329L protection cover 19 inch type, one unit 19 inch type, two units, side by side Matsushita product For portable power supply

*1: The K224 adapter is used to prevent damage to the input connector.

*2: The MF2400B series has the MP612A Fuse Holder (with MP613A Fuse Element) to prevent input of excessive power.

In addition, the MP612A Fuse Holder has an N-type connector, so an adapter is required according to the coupled connector type.

Specifications are subject to change without notice.

ANRITSU CORPORATION MEASUREMENT SOLUTIONS

5-10-27, Minamiazabu, Minato-ku, Tokyo 106-8570, Japan
 Phone: +81-3-3446-1111
 Telex: J34372
 Fax: +81-3-3442-0235

Overseas Subsidiaries

● U.S.A.

ANRITSU COMPANY

North American Region Headquarters

1155 East Collins Blvd., Richardson, Tx 75081, U.S.A.
 Toll Free: 1-800-ANRITSU (267-4878)
 Phone: +1-972-644-1777
 Fax: +1-972-671-1877

● Canada

ANRITSU ELECTRONICS LTD.

Unit 102, 215 Stafford Road West
 Nepean, Ontario K2H 9C1, Canada
 Phone: +1-613-828-4090
 Fax: +1-613-828-5400

● Brasil

ANRITSU ELETRÔNICA LTDA.

Praia de Botafogo 440, Sala 2401 CEP 22250-040,
 Rio de Janeiro, RJ, Brasil
 Phone: +55-21-5276922
 Fax: +55-21-537-1456

● U.K.

ANRITSU LTD.

200 Capability Green, Luton, Bedfordshire LU1 3LU, U.K.
 Phone: +44-1582-433200
 Fax: +44-1582-731303

● Germany

ANRITSU GmbH

Grafenberger Allee 54-56, 40237 Düsseldorf, Germany
 Phone: +49-211-96855-0
 Fax: +49-211-96855-55

● France

ANRITSU S.A.

9, Avenue du Québec Z.A. de Courtabœuf 91951 Les
 Ulis Cedex, France
 Phone: +33-1-60-92-15-50
 Fax: +33-1-64-46-10-65

● Italy

ANRITSU S.p.A.

Via Elio Vittorini, 129, 00144 Roma EUR, Italy
 Phone: +39-06-509-9711
 Fax: +39-06-502-24-25

● Sweden

ANRITSU AB

Botvid Center, Fittja Backe 1-3 145 84 Stockholm,
 Sweden
 Phone: +46-853470700
 Fax: +46-853470730

● Singapore

ANRITSU PTE LTD.

6, New Industrial Rd., #06-01/02, Hoe Huat Industrial
 Building, Singapore 536199
 Phone: +65-282-2400
 Fax: +65-282-2533

● Hong Kong

ANRITSU COMPANY LTD.

Suite 719, 7/F., Chinachem Golden Plaza, 77 Mody
 Road, Tsimshatsui East, Kowloon, Hong Kong, China
 Phone: +852-2301-4980
 Fax: +852-2301-3545

● Korea

ANRITSU CORPORATION

14F Hyun Juk Bldg. 832-41, Yeoksam-dong,
 Kangnam-ku, Seoul, Korea
 Phone: +82-2-553-6603
 Fax: +82-2-553-6604-5

● Australia

ANRITSU PTY LTD.

Unit 3/170 Forster Road Mt. Waverley, Victoria, 3149,
 Australia
 Phone: +61-3-9558-8177
 Fax: +61-3-9558-8255

● Taiwan

ANRITSU COMPANY INC.

6F, 96, Sec. 3, Chien Kou North Rd. Taipei, Taiwan
 Phone: +886-2-2515-6050
 Fax: +886-2-2509-5519

● Spain

ANRITSU ELECTRÓNICA, S.A.

Europa Empresarial Edificio Londres, Planta 1, Oficina 6
 C/ Playa de Liencres, 2 28230 Las Rozas. Madrid, Spain
 Phone: +34-91-6404460
 Fax: +34-91-6404461