

D.C. Power Supply

C1



GPC-1850D/3020D/3030D



GPC-3030DQ

FEATURES

- * Four Digital Panel Meters (GPC-3030DQ)
- * Triple Output
- * Auto Tracking
- * Auto Series and Parallel Operation
- * Constant Voltage and Constant Current Operation
- * Low Ripple and Noise
- * Internal Select for Continuous or Dynamic Load
- * Overload and Reverse Polarity Protection
- * Rotation Speed of the Fan is Controlled by Heatsink Temperature (Only European Specification)(GPC-3030DQ)
- * 3 1/2 Digits 0.39" LED Display(GPC-3030DQ)
- * 3 1/2 Digits 0.5" LED Display(GPC-1850D/3020D/3030D)
- * 5V, 3A Fixed Output

SPECIFICATIONS

OPERATION MODE	
Independent	Two independent outputs and 5V fixed output Output from 0 to rating volts and 0 to rating amperes
Series	Output from 0 to \pm rating volts at rating amperes each
Parallel	Output from 0 to double rating volts at rating amperes Output from 0 to double rating amperes at rating volts
5V FIXED OUTPUT	
Regulation	Line regulation $\leq 5\text{mV}$ Load regulation $\leq 10\text{mV}$
Ripple & Noise	$\leq 2\text{mVrms}$
Voltage Accuracy	$5\text{V} \pm 0.25\text{V}$
Output Current	3A
TRACKING OPERATION	
Tracking Error	$\leq 0.5\% + 10\text{mV}$ of the master
Series Regulation	$\leq 300\text{mV}$
CONSTANT VOLTAGE OPERATION	
Regulation	Line regulation $\leq 0.01\% + 3\text{mV}$ Load regulation $\leq 0.01\% + 3\text{mV}$ (rating current $\leq 3\text{A}$) $\leq 0.02\% + 5\text{mV}$ (rating current $\leq 10\text{A}$)
Ripple & Noise	$\leq 1\text{mVrms}$ 5Hz ~ 1MHz
Recovery Time	$\leq 100\mu\text{S}$ (50% Load change, Minimum load 0.5A)
CONSTANT CURRENT OPERATION	
Regulation	Line regulation $\leq 0.2\% + 3\text{mA}$ Load regulation $\leq 0.2\% + 3\text{mA}$
Ripple Current	$\leq 3\text{mA rms}$
METER	
Digital	3 1/2 digits 0.5" LED display 3 1/2 digits 0.39" LED display (for GPC-3030DQ) Accuracy $\pm (0.5\% \text{ of rdg} + 2 \text{ digits})$

INSULATION

Chassis and Terminal 20M Ω or above (DC 500V)
Chassis and AC Cord 30M Ω or above (DC 500V)

POWER SOURCE

AC 100V/120V/220V/240V $\pm 10\%$, 50/60Hz

ACCESSORIES

Instruction manual x 1 , Power cord x 1
Test lead GTL-105 x 1 ($\leq 3\text{A}$) , GTL-104 x 2 ($\leq 10\text{A}$)
European test lead GTL-203 x 1, GTL-204 x 2

DIMENSIONS

255(W) x 145(H) x 346(D) mm

ORDERING INFORMATION

Model	Independent	Series	Parallel	Weight (kg)
GPC-1850D 195W D.C. Power Supply	(0 ~ 18V/0 ~ 5A) x 2 , (5V/3A MAX) x 1	36V 5A	18V 10A	11.5
GPC-3020D 135W D.C. Power Supply	(0 ~ 30V/0 ~ 2A) x 2 , (5V/3A MAX) x 1	60V 2A	30V 4A	11.5
GPC-3030D 195W D.C. Power Supply	(0 ~ 30V/0 ~ 3A) x 2 , (5V/3A MAX) x 1	60V 3A	30V 6A	11.5
GPC-3030DQ 195W D.C. Power Supply	(0 ~ 30V/0 ~ 3A) x 2 , (5V/3A MAX) x 1	60V 3A	30V 6A	11.5

Strumenti di Misura Nuovi e Ricondizionati



Strada Vicinale Battifoglia Z.I.
06132 S. Andrea delle Fratte
Perugia

(39) 075 87 88 003 tel.
(39) 075 87 88 013 fax.
(39) 388 85 86 991 vendite
(39) 389 48 28 200 vendite
(39) 335 61 58 054 direzione

web. www.test.it
email. testinst@tin.it