

Patent No: 81011



FEATURES

- * 0.01% High Regulation
- * Constant Voltage and Constant Current Operation
- * Internal Select for Continuous or Dynamic Load
- * Low Ripple and Noise
- * Overload and Reverse Polarity Protection
- * 3 1/2 Digits 0.5" LED Display

GPR-H SERIES

SPECIFICATIONS

SPECIFICATIONS		
CONSTANT VOLTAGE OPERATION	Regulation	Line regulation $\leq 0.01\% + 3mV$ Load regulation $\leq 0.01\% + 5mV$ ($\leq 10A$) $\leq 0.02\% + 5mV$ ($\geq 10A$)
	Ripple & Noise Recovery Time Output Range	$\leq 1mVrms$ 5Hz ~ 1MHz $\leq 100 \mu S$ (50% Load change, Minimum load 0.5A) 0 to rating voltage continuously adjustable
CONSTANT CURRENT OPERATION	Regulation	Line regulation $\leq 0.2\% + 3mA$ Load regulation $\leq 0.2\% + 3mA$
	Ripple Current	$\leq 5mArms$ ($\leq 20A$), $\leq 10mArms$ ($\leq 30A$) $\leq 20mArms$ ($\leq 50A$)
	Output Range	0 to rating amperes continuously adjustable
METER	Digital	3 1/2 Digits 0.5" LED display Accuracy $\pm (0.5\% \text{ of rdg } + 2 \text{ digits })$
INSULATION	Chassis and Terminal Chassis and AC Cord	100M Ω or above (DC 1000V) 100M Ω or above (DC 1000V)
POWER SOURCE		AC 100V/120V/220V/240V $\pm 10\%$, 50/60Hz
ACCESSORIES		Instruction manual x 1, Power cord x 1 Test lead GTL-105 x 1 ($\leq 3A$) or GTL-104 x 1 ($\leq 10A$) or Not Available ($>10A$)
DIMENSIONS		225(W) x 145(H) x 420(D) mm

ORDERING INFORMATION

Model	Output Volts (V)	Output Amps (A)	Weight (kg)
GPR-0830HD 240W D.C. Power Supply	0 ~ 8	0 ~ 30	18.5
GPR-1820HD 360W D.C. Power Supply	0 ~ 18	0 ~ 20	18.5
GPR-3510HD 350W D.C. Power Supply	0 ~ 35	0 ~ 10	18.5
GPR-6060D 360W D.C. Power Supply	0 ~ 60	0 ~ 6	18.5
GPR-7550D 375W D.C. Power Supply	0 ~ 75	0 ~ 5	18.5
GPR-11H30D 330W D.C. Power Supply	0 ~ 110	0 ~ 3	13.5
GPR-30H10D 300W D.C. Power Supply	0 ~ 300	0 ~ 1	13.5

NOTE : Approved Only for GPR-1820HD, GPR-3510HD, GPR-7550D, GPR-11H30D

Strumenti di Misura Nuovi e Ricondizionati


 web. www.test.it
 email. testinst@tin.it

 Strada Vicinale Battifoglia Z.I.
 06132 S. Andrea delle Fratte
 Perugia

 (39) 075 87 88 003 tel.
 (39) 075 87 88 013 fax.
 (39) 388 85 86 991 vendite
 (39) 389 48 28 200 vendite
 (39) 335 61 58 054 direzione