

AC Millivolt Meter

D3



FEATURES

- * 300 μ V Full scale sensitivity
- * Measures frequency from 10Hz ~ 1MHz
- * Measures from -70dB ~ +40dB in 12 ranges
- * Dual Channel (GVT-427B)

GVT-427B(2CH)/GVT-417B(1CH)

SPECIFICATIONS

INPUT

Voltage Range	300 μ V~100V of Full Scale in 12 ranges
Decibel Range	-70dB ~ +40dB in 12 ranges
Accuracy	$\pm 3\%$ of full scale
Operating Mode	Channel 1 and 2 separately or simultaneously at channel 1 one channel only (GVT - 417B)
Frequency Responses	20Hz~200kHz $\pm 3\%$, 10Hz~1MHz $\pm 10\%$ (reference 1 kHz)
Impedance	1M Ω , approx, 40pF

OUTPUT

Level	Approx. 0.1Vrms at full scale
Distortion	Less than 2%

POWER SOURCE

AC 115/230V $\pm 10\%$, 50/60Hz

ACCESSORIES

Instruction Manual x 1
Power cord x 1
Test Lead GTL-101 x 2
(GTL-101 x 1 for GVT - 417B)

DIMENSIONS & WEIGHT

130(W) x 210(H)x295(D)mm; Approx. 2.7 kg

ORDERING INFORMATION

GVT-427B	2 Channels AC Millivolt Meter
GVT-417B	1 Channel AC Millivolt Meter

NOTE :  mark is only for GVT-417B

Strumenti di Misura Nuovi e Ricondizionati



web. www.test.it
email. testinst@tin.it

Strada Vicinale Battifoglia Z.I.
06132 S. Andrea delle Fratte
Perugia

(39) 075 87 88 003 tel.
(39) 075 87 88 013 fax.
(39) 388 85 86 991 vendite
(39) 389 48 28 200 vendite
(39) 335 61 58 054 direzione