



DDS Function Generator

NEW



CE

SFG-2104/2107/2110 (4/7/10MHz)

NEW



CE

SFG-2004/2007/2010 (4/7/10MHz)

FEATURES

- * DDS Technology and FPGA Chip Design
- * Frequency Range: 0.1Hz~4MHz/7MHz/10MHz
- * High Frequency Accuracy : ± 20 ppm
- * High Frequency Stability : ± 20 ppm
- * Frequency Resolution : 100mHz
- * Low Distortion Sine Wave : -55dBc, 0.1Hz~200KHz
- * Built-in 6 Digits, 150MHz/High Resolution Counter (SFG-2100 Series Only)
- * INT/EXT AM/FM Modulation (SFG-2100 Series Only)
- * LIN/LOG Sweep Mode (SFG-2100 Series Only)
- * Front Panel Setting Save/Recall with 10 Groups of Setting Memories

SPECIFICATIONS

		SFG-2000 Series			SFG-2100 Series		
		SFG-2004	SFG-2007	SFG-2010	SFG-2104	SFG-2107	SFG-2110
MAIN	Frequency	0.1Hz~4MHz	0.1Hz~7MHz	0.1Hz~10MHz	0.1Hz~4MHz	0.1Hz~7MHz	0.1Hz~10MHz
	Range(For Sine, Square) Range(For Triangle) Resolution Stability Accuracy Aging	0.1Hz~1MHz 0.1Hz ± 20 ppm ± 20 ppm ± 5 ppm / year					
	Output Function Amplitude Range Flatness(Sinewave relative to 1kHz) Impedance Attenuator DC Offset Duty Control Display	Sine, Square, Triangle 10Vpp(into 50 Ω load) $< \pm 0.3$ dB, 0.1Hz~1MHz; $< \pm 0.5$ dB, 1MHz~4MHz; $< \pm 2$ dB, 4MHz~10MHz 50 $\Omega \pm 10\%$ -20dB ± 1 dB $\times 2$ $< -5V \sim > +5V$ (into 50 Ω load) 20% to 80% below 1MHz (Square wave only) 1% 9 digits LED display					
SINE WAVE	Harmonics Distortion	-55dBc, 0.1Hz~200kHz; -40dBc, 0.2MHz~4MHz; -30dBc, 4MHz~10MHz (Specification applied from MAX. to 1/10 level)					
TRIANGLE WAVE	Linear	$\geq 98\%$, 0.1Hz~100kHz; $\geq 95\%$, 100kHz~1MHz					
SQUARE WAVE	Symmetry	$\pm 1\%$ of period +4ns to 0.1Hz~100kHz; Rise or Fall Time ≤ 25 ns at maximum output.(into 50 Ω load)					
CMOS OUTPUT	Level	4Vpp ± 1 Vpp~14.5Vpp ± 0.5 Vpp adjustable; Rise or Fall Time; ≤ 120 ns					
TTL OUTPUT	Level	≥ 3 Vpp; Fan Out; 20 TTL load; Rise or Fall Time; ≤ 25 ns					
SWEEP OPERATION	Sweep/Rate Sweep/Time Sweep/Mode	—			100:1 ratio max. and adjustable 0.5Sec~30Sec adjustable Lin./Log. switch selector		
AMPLITUDE MODULATION	Depth & MOD. Frequency Carrier BW EXT Sensitivity	—			0~100% ; 400Hz(INT), DC~1MHz(EXT) 100Hz~5MHz(-3dB) ≤ 10 Vpp for 100% modulation		
FREQUENCY MODULATION	Deviation & MOD. Frequency EXT Sensitivity	—			0~ $\pm 5\%$; 400Hz(INT), 1kHz(EXT) ≤ 10 Vpp for 10% modulation		
FREQUENCY COUNTER	Range Accuracy Time base Resolution Input Impedance Sensitivity	—			5Hz~150MHz Time base accuracy ± 1 count ± 20 ppm(23 $^{\circ}$ C $\pm 5^{\circ}$ C) after; 30 minutes warm up The maximum resolution is 10nHz for 1Hz and 0.1Hz for 100MHz 1M Ω /150pf ≤ 35 mVrms(5Hz~100MHz) ≤ 45 mVrms(100MHz~150MHz)		
STORE/RECALL FUNCTION		10 groups of Setting memories					
POWER SOURCE		AC115V, 230V $\pm 15\%$, 50/60Hz					
ACCESSORIES		Instruction manualx1, Power Cord x 1, GTL-101x1			Instruction manualx1, Power Cord x 1, GTL-101x2		
DIMENSION & WEIGHT		107(W) \times 266(H) \times 293(D) m/m; Approx. 3.1kg			107(W) \times 266(H) \times 293(D) m/m; Approx. 3.2kg		

ORDERING INFORMATION

SFG-2004	4MHz DDS Function Generator	SFG-2104	4MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
SFG-2007	7MHz DDS Function Generator	SFG-2107	7MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation
SFG-2010	10MHz DDS Function Generator	SFG-2110	10MHz DDS Function Generator with Counter, Sweep & AM, FM Modulation