

Digital Multimeter



GDM-8034 (3 1/2 Digits)

SPECIFICATIONS	
DC VOLTAGE	
Range	200mV, 2V, 20V, 200V, 1000V 5 ranges
Accuracy	$\pm(0.5\% \text{ rdg} + 1 \text{ digit})$
Input Impedance	10M Ω
AC VOLTAGE	
Range	200mV, 2V, 20V, 200V, 750V 5 ranges
Accuracy	40Hz ~ 500Hz $\pm(1\% \text{ rdg} + 4 \text{ digits})$
Input Impedance	10M Ω
DC CURRENT	
Range	200 μ A, 2mA, 20mA, 200mA, 2A, 20A 6 ranges
Accuracy	200 μ A ~ 200mA $\pm(0.5\% \text{ rdg} + 1 \text{ digit})$ 2A ~ 20A $\pm(1\% \text{ rdg} + 3 \text{ digits})$
AC CURRENT	
Range	200 μ A, 2mA, 20mA, 200mA, 2A, 20A 6 ranges
Accuracy	40Hz ~ 500Hz on all ranges 200 μ A ~ 200mA $\pm(1\% \text{ rdg} + 4 \text{ digits})$ 2A ~ 20A $\pm(1.5\% \text{ rdg} + 2 \text{ digits})$
RESISTANCE	
Range	200 Ω , 2k, 20k, 200k Ω , 2M Ω , 20M Ω 6 ranges
Accuracy	200 Ω ~ 2M Ω $\pm(0.75\% \text{ rdg} + 1 \text{ digit})$ 20M Ω $\pm(1.5\% \text{ rdg} + 5 \text{ digits})$
CAPACITANCE	
Range	2nF, 20nF, 200nF, 2 μ F, 20 μ F 5 ranges
Accuracy	$\pm(2\% \text{ rdg} + 4 \text{ digits})$
Test Freq.	300Hz $\pm 5\%$
DIODE TEST	
Test Current	Max. 2.5mA
Open Voltage	Max. 3.2V
CONTINUITY BEEPER	
Description	Buzzer sounds if conductance less than 30 Ω
Test Current	Max. 2.5 mA
Open Voltage	Max. 3.2V
DISPLAY	
0.5" LCD display	
POWER SOURCE	
AC 110V/220V $\pm 15\%$, 50/60Hz	
ACCESSORIES	
Instruction manual x 1, Power cord x 1, Test lead GTL-107A x 1	
DIMENSIONS & WEIGHT	
245(W) x 95(H) x 280(D) mm, Approx. 2kg	

FEATURES

- * 8 Functions AC/DC Voltage, AC/DC Current, Resistance Capacitance, Diode Test and Audible Continuity Beeper
- * High Voltage 1000V and 20A Current Range
- * 0.5% Basic DCV Accuracy
- * LCD Display

ORDERING INFORMATION

GDM-8034 3 1/2 Digits LCD Digital Multimeter

Strumenti di Misura Nuovi e Ricondizionati



Strada Vicinale Battifoglia Z.I.
06132 S. Andrea delle Fratte
Perugia

(39) 075 87 88 003 tel.
(39) 075 87 88 013 fax.
(39) 388 85 86 991 vendite
(39) 389 48 28 200 vendite
(39) 335 61 58 054 direzione

web. www.test.it
email. testinst@tin.it