

Data Sheet

VIAVI OneExpert ONX-580

For xDSL, G.fast and FTTH

Fast, consistent, and complete!

Consistently achieve high-performance results when deploying ultra-fast residential broadband over xDSL, G.fast, and FTTH.

OneExpert[™] helps field technicians fix problems right the first time, every time. A multitouch, user- friendly interface and OneCheck[™] automated tests ease complex tasks with clear pass/fail results. And, its future-proof modules ensure years of use supporting access and home networks.

Open, Modular Design

OneExpert offers the advantages of integrated cloud-based applications, touch screen interfaces, smartphones, and tablets. OneExpert helps technicians perform more efficiently and fix problems faster while ensuring service providers can invest in a long-term, open platform. Modular hardware means the meter can be updated as technology is updated. Software can be upgraded and enhanced in the field, so no down-time for these changes.

Key Benefits and Features

- Modular platform scales for new WiFi, fiber, and xDSL technology including VDSL Profile 35b and G.fast
- OneCheck automates field tests and simplifies Copper and DSL results to consistently close jobs correctly
- One button OneCheck TDR auto identifies fault types and locations right away
- Prove the true customer experience with a standardized TrueSpeed[™] test (RFC-6349)
- OneExpert[™] app uses everyday mobile devices for remote control, data enhancements, and connectivity
- StrataSync[™] cloud-enabled asset and test data management provides visibility for test results and completed tasks and keeps track of used instrument inventory



StrataSync – cloud-based asset and data management

Bluetooth/WiFi ready connectivity

xDSL Testing up to G.fast

A sync test is essential in characterizing DSL link quality (bandwidth rates, margins, errors, and likelihood for errors). This test also helps determine whether issues are coming from the equipment (CPE or DSLAM/DPU ports) or from the profile settings. It shows important results on a single DSL summary screen page. The test uncovers errors (CRC, FEC, LOS, LOF, and LOM) that impact application layers such as IP video.

Module	ONX-BDCM- DSL-ANXAB xDSL Annex B	ONX580-BDCM- DSL-BONDED xDSL Annex A Bonded	ONX-BDCM- GFAST Broadcom V35b/G.fast 106	ONX-TM-GFAST BDCM/SCKPIO V35b/G.fast 106	ONX-TM- SCKP-212 BDCM/SCKPIO V35b/G.fast 212	
ADSL	•	•	•	•	•	
ADSL/VDSL Anx A/M/L (to 30a)	•	•	•	•	•	
ADSL/VDSL Anx B/J (to 30a)	•	_	■ 1	1	■1	
ADSL2 Bonded Anx A/M/L	_	•	•	•	•	
VDSL2 Bonded Anx A/M/L (to 17a)	_	•	•	•	•	
V35b	_	_	•	•	•	
V35b Bonded	_	_	_	_	•	
BDCM G.fast 106MHz	_	_	•	•	•	
Sckipio G.fast 106MHz	_	_	_	•	•	
BDCM G.fast 212MHz	_	_	_	_	•	
Sckipio G.fast 212MHz	_	_	_	_	•	
BDCM 106MHz Bonded	_	_	_	_	•	
Sckipio 106MHz Bonded	_	_	_	_	•	

¹Annex B/J Compatible

Specifications

Power Supply					
Battery	Li-ion internal rechargeable, 7.4 V nominaL voltage, 6600 mAh				
Operating time >4 hours for typical use cases					
Auto power down (adjustable)					
AC line operation via external adapter/car charger					
Connector					
DSL test module	Varies by module (8 Pin Modular and 6 Pin Modular)				
Ethernet	2 x 8-pin modular (RJ45)				
T/A, R/B, T1/A1, R1/B1 and ground/Earth	2 mm recessed banana				
POTS	8-pin modular (RJ45) and tip A – ring B				
USB	2 x USB 2.0 client ports				
Connectivity					
USB flash drive					
Remote operation					
Mobile device application					
Bluetooth					
Standard	Bluetooth 2.1 + EDR, Bluetooth 4.0 ready				
WiFi					
Standard	802.11 a/b/g/n (2.4/5 GHz)				
Audio Support					
Speaker/microphone					
Bluetooth headset					
Permissible Ambient Temperature					
Nominal range of use	0 to 50°C (32 to 122°F)				
Storage and transport	-10 to 60°C (14 to 140°F)				
Humidity					
Operating humidity	10 to 90%				
Water/Dust Ingress					
Complies with IP54	Designed to comply with IP54				
Display	127 mm (5 in) diagonal color WVGA (800 x 480 pixels) backlit LCD with projected capacitive multitouch screen				

Ordering Information

The OneExpert can be ordered fully configured for high-end ADSL2+ /VDSL2 /G.fast and copper test demands or scaled for specific needs and applications, such as all fiber only without copper.

Included Test Applications

(all mainframes and package orders except noted differently below)

Fiber Tests

- OneCheck Fiber
- Power meter (via Accessory)
- OTDR (via Accessory)
- Inspection (via Accessory)

Copper on mainframe ONX-580

- TDR
- OneCheck Copper
- DVOM
- Opens
- Longitudinal balance
- Load coil
- POTS TDR

Wiring Tools

- Wire map on mainframe ONX-580
- Hub flash
- Port discovery
- Ping tool

IP Data Tests

- Web browser
- IP ping
- FTP/HTTP speed test
- OneCheck Ethernet

WiFi

- Scan
- Access point
- WiFi Advisor support

Coax — SmartID

- Locate IDs
- Single-ended coax map
- Dual-ended coax map
- Whole home check

StrataSync

 StrataSync Core Asset and Data Management

Mainframe				
OneExpert; ONX-580 Pro ¹	ONX-580P			
OneExpert; ONX-580 ¹	ONX-580			
OneExpert; ONX-580A ¹	ONX-580A			
Module				
OneExpert Broadcom 63158/Sckipio V.35B/G.fast Amendment 3 module (bonded ready)	ONX-TM-SCKP-212			
OneExpert Broadcom 63138 G.fast/V.35B test module	ONX-BDCM-GFAST			
OneExpert Broadcom 63168 (bonded ready) test module	ONX580-BDCM-DSL-BONDED			
OneExpert Broadcom 63168 (VDSL, ADSL2+ ANX A/B) test module	ONX-BDCM-DSL-ANXAB			
OneExpert cover module	ONX-COVER			
Software Options				
ADSL/VDSL bonding option for module ONX-BDCM-DSL-BONDED	ONX580-BONDED			
Broadcom G.fast option	ONX580-GFAST			
Sckipio G.fast option	ONX580-SCKIPIO			
V.35b option	ONX580-V35B			
G.fast Amendment 3 Option	ONX580-GFAST-212			
DSL Helper Utility	ONX580-DSL-HELPER			
Mobile device connectivity	ONX580-MOBILE-001			
Bluetooth	ONX580-BLUETOOTH			
HPNA	ONX580-HPNA			
TrueSpeed	ONX-TRUESPEED			
Ookla SpeedTest	ONX-OOKLA-SPEEDTEST			
Broadcom Speedservice	ONX-SPEED-SERVICE			
VIAVI Speedcheck	ONX-SPEEDCHECK			
Smart Access Anywhere	ONX-SMART-ACCESS			
HighFrequency SmartID Testing ²	ONX-SMARTID-MOCA			
IP video	ONX580-IPVIDEO			
VoIP	ONX-VOIP			
MOS ³	ONX-MOS			
Resistive fault locator	ONX580-RFL			
Transmission impairments and spectral ⁴	ONX580-TIMS			
Copper Expert software	ONX580-COPPER-EXPERT			
Cables				
Dual Pair Bed of Nails Copper Cables	CB-DUAL-BON			
Single Pair Bed of Nails Copper Cables	CB-SINGLE-BON			
Dual Pair Telco Clips Copper Cables	CB-DUAL-TELCO			
Single Pair Telco Clips Copper Cables	CB-SINGLE-TELCO			
Dual Pair Banana Copper Cables	CB-DUAL-4MM			
Single Pair Banana Copper Cables	CB-SINGLE-4MM			
Telco clip package for 4 mm banana	CB-CLIPS			

Spectral monitor cable	CB-SPE-MON			
Dual Pair Bed of Nails 8 Pin to Banana Cables	CB-DSL8-4MM			
Dual Pair Bed of Nails 8 Pin to Telco Clip Cables	CB-DSL8-TELCO			
Dual Pair Bed of Nails 8 Pin to Bed of Nails Cables	CB-DSL8-BON			
Dual Pair Bed of Nails 6 Pin to Banana Cables	ONX-DSL6-4MM			
Dual Pair Bed of Nails 6 Pin to Bed of Nails Cables	ONX-DSL6-BON			
SmartID USB cable 6 ft	SMARTID-USBCABLE-6FT			
SmartID USB cable 3 ft	SMARTID-USBCABLE-3FT			
Accessories				
Battery	ONX580-BATTERY-48WH			
AC universal power adapter	AC-CHARGER			
Large carrying case	CC-034601			
Small carrying case	CC-CARRYING-CASE-SMALL			
Soft glove	AC-GLOVE			
Strand hook	AC-STRANDHOOK			
Hand strap	AC-HANDSTRAP			
Shoulder strap	AC-005101			
Car adapter	AC-CAR-CHARGER			
Bluetooth headset	AC-BLUETOOTH-HEADSET			
SmartID Plus incl. micro USB cable	SMARTID-PLUS-1PC-TELCO			
SmartID Plus 1 unit	SMARTID_PLUS_1PC			
SmartID, 6 units	SMARTID-6PC-TELCO-KIT			
SmartID accessory kit	SMARTID-ACCKIT-TELCO			
Wire mapping smart remote; RJ11, RJ45	AC-WIREMAP-REMOTE			
UFEDIIB bonded far end device with standard accessories	UFEDIIB-PKG-1			
SDI-100 WAND	SDI-100			
SmartOTDR SL – Wireless OTDR	ESL18FA65-APC			
MP-60 – USB optical power meter	MP-60A			
P5000i – USB fiber scope	FBP-P5000I			
WiFi Advisor				
WiFi Advisor Basic Package	WFED300AC-1PC			
WiFi Advisor Installer Package	WFED300AC-2PC			
Services and Support Plans				
Bronze Support Plan 5 years	BRONZE-5			
Silver Support Plan 3 years	SILVER-3			
Silver Support Plan 5 years	SILVER-5			

¹Includes test applications as specified above. Requires selection of battery, AC universal power adapter, and power cord.

²Requires SmartID and SmartID Plus to be ordered separately.

³Requires VoIP software option.

⁴Enables copper RX tones, spectral, WB noise, wideband impulse noise, wideband impulse noise capture.

VIAVI Care Support Plans

Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

For more Information: go to viavisolutions.com/viavicareplan

Features *5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration	Accessory Coverage	Express Loaner
BronzeCare	Technician Efficiency	Premium	✓	✓	√				
SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	✓	√ *	✓		
MaxCare	High Availability	Premium	✓	√	√	✓*	√	✓	√



Contact Us

+1 844 GO VIAVI (+1 844 468 4284)

To reach the VIAVI office nearest you, visit viavisolutions.com/contact

© 2020 VIAVI Solutions Inc. Product specifications and descriptions in this document are subject to change without notice. oneexpert-ds-cab-tm-ae 30175818 909 0120